## **VF** Series



VF is a watertight primary seal system for vertical expansion joint conditions. It is great for parking garages, retrofit joints, plaza decks, stadiums, and other watertight applications.

#### **Advantages**

- Watertight and durable primary seal
- Quick and easy installation
- Coated with factory-applied sealant that is chemical resistant and UV stable
- Fire rated model (VFR) is available







Construction Specialties

Questions? Connect with a CS Representative. c-sgroup.com/representative-locator c-sgroup.com | 800.233.8493 ©2024 Construction Specialties, Inc.

# **VF** Series

#### **Product Details**

- Joint sizes range from 1" to 8" (25.4mm to 203.2mm)
- 6' 6" (2m) stock lengths
- VF-100 (1" model) is supplied in 10' reel lengths
- Meets ASTM E1399



### **Color Options**



See all finish options online at c-sgroup.com.

#### Warranty

• Standard Five-Year Warranty



**Model Details** 

Wall to Wall

MODEL	WALL TO WALL	FIRE RATED
VF	٠	
VFR	•	•









S Construction Specialties<sup>•</sup>

Questions? Connect with a CS Representative. c-sgroup.com/representative-locator

c-sgroup.com | 800.233.8493 ©2024 Construction Specialties, Inc.

 $\rightarrow$