

Privacy Curtains + Track



Construction Specialties®


Compare Privacy Curtains + Track

PRODUCT NAME	TRADITIONAL CURTAINS	ON THE RIGHT TRACK® CURTAIN	HUSH CURTAIN®	SNAP LOCK CURTAINS	DISPOSABLE CURTAIN	SHOWER CURTAINS
Standard Panel Width	69"	69"	3' - 5' sections	69"	Up to 100"	42" or 71"
Available in CSelect Fabric	•	•	•	•	8 Disposable Options	
Easy Removal/ Clean		•	Select Models	•	Select Models	Select Models
Standard Mesh Height	18", 21", 28", 30"	19", 3.5" header	0-36"	0-36"	23"	N/A
Standard Height	Up to 74"	73"	Up to 74"	69"	77"	74"

PRODUCT NAME	STANDARD TRACK	ON THE RIGHT TRACK	QWIK SWITCH	NARROWLINE TRACK	SURFACE MOUNTED IV TRACK
Size	1 3/8" x 3/4"	3/8" x 1 1/2"	1 3/8" x 3/4"	29/32" x 1 1/16"	1 3/8" x 3/4"
Radius Available	•	•	•	•	•
Finish Options	Anodized Aluminum White Powder Coat	White Powder Coat	Anodized Aluminum White Powder Coat	Anodized Aluminum White Powder Coat	Anodized Aluminum White Powder Coat
Mount	Surface Suspended	Suspended	Surface	Surface Suspended	Surface



Compare Privacy Curtains + Track

						
PRODUCT NAME	CARRIER GATE	CARRIER STOP	GRID CEILING CLIP	SPLICE	OFFSETS	WALL SOCKET
Model	CGATE	CSTOP	GCCLIP		OFFSET	
Details	Used at all curtain stacking points. Assembled with machine screw. Provides easy insertion or removal of carrier.	Used at the ends of curtain tracks or bends. Made of molded nylon or aluminum.	Allow for quick & easy installation of the suspended aluminum track to horizontal regular tile grids (T-grids).	6" (152.4mm) splices are used where one-piece sections are not long enough or where radius & straight tracks connect.	Used to wrap track around the foot of the bed. 30° - 45° are supplied 2' x 2' (0.61m x 0.61m) after the 12" (304.8mm) radius. Can be supplied in custom lengths.	Nylon socket designed to secure suspended mounted track systems to the wall.
Finish Options	<ul style="list-style-type: none"> • Gray • White • Aluminum • Custom 	<ul style="list-style-type: none"> • Gray • White • Aluminum • Custom 	<ul style="list-style-type: none"> • Gray • White 	<ul style="list-style-type: none"> • Anodized Aluminum • White Powdercoat 	<ul style="list-style-type: none"> • Anodized Aluminum • White Powdercoat 	<ul style="list-style-type: none"> • Gray • White

							
NARROW-LINE CARRIER	GENERAL CARRIER	SPOL CARRIER	BREAKAWAY CARRIER	BREAKAWAY CARRIER	CURTAIN TIEBACK	BEADED CHAIN DROP	SHOWER CURTAIN ROD
NCAR 1062	STD CAR 1075	SPCAR 6062	BCAR SB062	BCAR SPC30			
Combines a nylon axle & a wheel with a nickel-plated brass bead chain & polished aluminum hook.	A super-smooth economical carrier manufactured completely from nylon, including nylon axle wheels.	Manufactured from Nylon/Delrin®, these carriers provide fast, free movement.	For use in behavioral health spaces. The hook is designed to pop out of the axle when 8 to 10 lbs. of pressure is applied.	For use in behavioral health spaces. This patented carrier is designed to pop out on one side when 8.5 to 10.5 lbs. of pressure is applied.	Two options to match the design of curtain. Lengths are fabricated to accommodate the width of curtain.	For instances where NFPA* standards are required, this product can be used on curtains as a substitute for traditional nylon mesh.	1" (26mm) and 1 1/4" (31.75mm) outer diameter stainless steel Shower Curtain Rods with radius options available. Five ball shower hooks standard.



Construction Specialties®

c-sgroup.com | 800.233.8493