

# TBP Converting, Inc. Sikaflex 552 SDS

### Sikaflex®-552

Revision Date 03/11/2015



#### 1. Identification

Product name	:	Sikaflex <sup>®</sup> -552
Supplier	:	Sika Corporation
Address	:	201 Polito Avenue Lyndhurst, NJ 07071 USA www.sikausa.com
Telephone	:	(201) 933-8800
Telefax	:	(201) 804-1076
Emergency telephone	:	CHEMTREC: 800-424-9300 INTERNATIONAL: 703-527-3887 ehs@sika-corp.com
Recommended use of the chemical and restrictions on use	:	For further information, refer to the product technical data sheet.

#### 2. Hazards identification

GHS Classification	
Skin sensitization , Category 1 Carcinogenicity , Category 2	H317: May cause an allergic skin reaction. H351: Suspected of causing cancer.
GHS Label element	
Hazard pictograms	
Signal Word	: Warning
Hazard Statements	: H317 May cause an allergic skin reaction. H351 Suspected of causing cancer.
Precautionary Statements	<ul> <li>Prevention:</li> <li>P201 Obtain special instructions before use.</li> <li>P202 Do not handle until all safety precautions have been read and understood.</li> <li>P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.</li> <li>P272 Contaminated work clothing must not be allowed out of the workplace.</li> <li>P280 Wear protective gloves.</li> <li>P281 Use personal protective equipment as required.</li> <li>Response:</li> <li>P302 + P352 IF ON SKIN: Wash with plenty of soap and water.</li> <li>P308 + P313 IF exposed or concerned: Get medical advice/ attention.</li> </ul>

Revision Date 03/11/2015



P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P363 Wash contaminated clothing before reuse.
Storage:
P405 Store locked up.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

See Section 11 for more detailed information on health effects and symptoms. There are no hazards not otherwise classified that have been identified during the classification process.

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

#### 3. Composition/information on ingredients

Pure substance/mixture : Mixture

#### **Hazardous ingredients**

Chemical Name	CAS-No.	Concentration (%)
Carbon black	1333-86-4	>= 2 - < 5 %
titanium dioxide	13463-67-7	>= 2 - < 5 %
Aminoalkylmethoxysilane	1760-24-3	>= 0 - <= 1 %

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

#### 4. First aid measures

If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	<ul> <li>Take off contaminated clothing and shoes immediately.</li> <li>Wash off with soap and plenty of water.</li> <li>If symptoms persist, call a physician.</li> </ul>
In case of eye contact	<ul> <li>Remove contact lenses.</li> <li>Keep eye wide open while rinsing.</li> <li>If eye irritation persists, consult a specialist.</li> </ul>
If swallowed	<ul> <li>Clean mouth with water and drink afterwards plenty of water. Induce vomiting immediately and call a physician. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.</li> </ul>
Most important symptoms and effects, both acute and delayed	: sensitizing effects
-	Allergic reactions See Section 11 for more detailed information on health effects

### Safety Data Sheet

### Sikaflex<sup>®</sup>-552

Revision Date 03/11/2015 Print Date 03/11/2015 and symptoms. Protection of first-aiders : Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attendance. : Treat symptomatically. Notes to physician 5. Fire-fighting measures Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Specific extinguishing : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. methods Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Special protective equipment : In the event of fire, wear self-contained breathing apparatus. for fire-fighters 6. Accidental release measures Personal precautions, : Use personal protective equipment. protective equipment and Deny access to unprotected persons. emergency procedures : Do not flush into surface water or sanitary sewer system. Environmental precautions If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained. Methods and materials for : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). containment and cleaning up Keep in suitable, closed containers for disposal. 7. Handling and storage Advice on safe handling : Do not breathe vapors or spray mist.

Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.

# Sikaflex®-552



Conditions for safe storage	<ul> <li>Store in original container.</li> <li>Keep container tightly closed in a dry and well-ventilated place.</li> <li>Containers which are opened must be carefully resealed and kept upright to prevent leakage.</li> <li>Observe label precautions.</li> <li>Store in accordance with local regulations.</li> </ul>
Materials to avoid	: No data available

#### 8. Exposure controls/personal protection

Component	CAS-No.	Basis **	Value	Exposure limit(s)* / Form of exposure
Carbon black	1333-86-4	ACGIH	TWA	3.5 mg/m3
		OSHA Z-1	TWA	3.5 mg/m3
		OSHA P0	TWA	3.5 mg/m3
		ACGIH	TWA	3 mg/m3 Inhalable fraction
titanium dioxide	13463-67-7	OSHA P0	TWA	10 mg/m3 Total
		OSHA Z-1	TWA	15 mg/m3 total dust
		OSHA P0	TWA	10 mg/m3 Total dust
		ACGIH	TWA	10 mg/m3

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### \*\*<u>Basis</u>

ACGIH. Threshold Limit Values (TLV) OSHA P0. Table Z-1, Limit for Air Contaminat (1989 Vacated Values) OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant OSHA P2. Permissible Exposure Limits (PEL), Table Z-2 OSHA Z3. Table Z-3, Mineral Dust

Engineering measures	: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
	recommended or statutory limits.

Revision Date 03/11/2015



Personal protective equipment		
Respiratory protection	Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.	
	The filter class for the respirator must be suitable for maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise whe the product. If this concentration is exceeded, self-or breathing apparatus must be used.	en handling
Hand protection Remarks	Chemical-resistant, impervious gloves complying w approved standard should be worn at all times whe chemical products if a risk assessment indicates th necessary.	n handling
Eye protection	Safety eyewear complying with an approved standar be used when a risk assessment indicates this is n	
Skin and body protection	Choose body protection in relation to its type, to the concentration and amount of dangerous substance the specific work-place.	
Hygiene measures	Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after h product. Remove contaminated clothing and protective equi before entering eating areas. Wash thoroughly after handling.	0

#### 9. Physical and chemical properties

Appearance	:	viscous
Color	:	various
Odor	:	very faint
Odor Threshold	:	No data available
Flash point	:	> 214 °F (> 101 °C)
Ignition temperature	:	Not applicable
Decomposition temperature	:	No data available
Lower explosion limit (Vol%)	:	No data available
Upper explosion limit (Vol%)	:	No data available
Flammability (solid, gas)	:	No data available
Oxidizing properties	:	No data available

Revision Date 03/11/2015



Autoignition temperature	:	No data available
рН	÷	Note: Not applicable
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Vapor pressure	:	Note: Not applicable
Density	:	ca.1.45 g/cm3 at 68 °F (20 °C)
Water solubility	:	Note: insoluble
Partition coefficient: n- octanol/water	:	No data available
Viscosity, dynamic	:	Note: Not applicable
Viscosity, kinematic	:	Note: Not applicable
Relative vapor density	:	No data available
Evaporation rate	:	No data available
Burning rate	:	No data available
Volatile organic compounds (VOC) content	:	19.5 g/l

#### 10. Stability and reactivity

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions.
Conditions to avoid	: No data available
Incompatible materials	: No data available

### 11. Toxicological information

Acute toxicity	
Product:	
Acute oral toxicity	: No data available
Acute inhalation toxicity	: No data available
Acute dermal toxicity	: No data available

Revision Date 03/11/2015



Ingredients: Carbon black: Acute oral toxicity	: LD50 Oral (Rat): > 8,000	ma/ka
,		5 5
Aminoalkylmethoxysilane: Acute oral toxicity	: LD50 Oral (Rat): ca. 2,40	0 mg/kg
Acute inhalation toxicity	: LC50: 1.49 mg/l Exposure time: 4 h Test atmosphere: dust/mi	st
Acute dermal toxicity	: LD50 Dermal (Rat): > 2,0	00 mg/kg
Skin corrosion/irritation		
<u>Product:</u> Remarks: No data available		
Serious eye damage/eye irr	itation	
<u>Product:</u> Remarks: No data available		
Respiratory or skin sensitiz	ation	
<u>Product:</u> Remarks: May cause an aller	aic skin reaction	
Remarks. May cause an aller	gic skill reaction.	
Germ cell mutagenicity		
Product:		
Germ cell mutagenicity - Assessment	: No data available	
Carcinogenicity		
Product:		
Carcinogenicity - Assessment	: Suspected of causing cancer.	
IARC	Group 2B: Possibly carcinogenic to humans	
NTP	Carbon black titanium dioxide Not applicable	1333-86-4 13463-67-7
Reproductive toxicity		
Product:		
Reproductive toxicity - Assessment	: No data available	

No data available

Revision Date 03/11/2015



#### STOT-single exposure

#### Product:

Assessment: No data available

#### STOT-repeated exposure

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

#### Product:

Assessment: No data available

#### Aspiration toxicity

#### Product:

No data available

#### 12. Ecological information

Other information		Do not empty into drains; dispose of this material and its container in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Component:		
Carbon black	1333-86-4	<u>Toxicity to fish:</u> LC50 Species: Brachydanio rerio (zebrafish) Dose: > 1,000 mg/l Exposure time: 96 h

13. Disposal considerations	
Disposal methods	
Waste from residues	<ul> <li>Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.</li> </ul>
Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal.

#### 14. Transport information

#### **DOT** Not dangerous goods

### Sikaflex®-552

Revision Date 03/11/2015



IATA Not dangerous goods IMDG Not dangerous goods

Special precautions for user No data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

#### 15. Regulatory information

TSCA list

: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

#### EPCRA - Emergency Planning and Community Right-to-Know

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

#### SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards :	Chronic Health Hazard Acute Health Hazard
SARA 302 :	No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 313 :	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
Clean Air Act	
Ozone-Depletion Potential	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

California Prop 65WARNING! This product contains a chemical known in the<br/>State of California to cause cancer.<br/>WARNING: This product contains a chemical known in the<br/>State of California to cause birth defects or other reproductive<br/>harm.

Revision Date 03/11/2015



#### 16. Other information

**HMIS Classification** 

Health	*	2
Flammability		1
Physical Hazard		0
Personal Protect	ion	x

**Caution:** HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

#### Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 03/11/2015

Material number: 468725