

Model BG-30

Acrovyn bumper guards and bed locators are designed to keep carts and beds away from walls and are perfect for chair rail applications where specific damage is recurring. The continuous aluminum retainer is mounted on bumper cushions for additional shock-absorption.

### **Advantages**

- Shock absorbing; designed to take impact
- Light duty crash rail
- Extensive variety of profile and finish options including Acrovyn and real wood, provides a solution for any design need
- Cover snaps over a continuous aluminum retainer
- Custom finishes available on wood models
- Factory-finished wood available with low VOC waterbased wood finishes

## **Applications**

- Chair rails
- Office
- Conference rooms
- Reception areas

# **Building Segments**

- Healthcare
- Senior Living
- Office & Mixed Use
- Retail
- Hospitality
- Aviation & Transportation



Learn More



**Construction Specialties** 

c-sgroup.com | 800.233.8493 ©2023 Construction Specialties, Inc.

### **Product Details**

- PVC-free Acrovyn in shadowgrain texture
- .078" (1.98mm) thick Acrovyn<sup>®</sup> cover & end caps
- Factory-formed radius
- 90- & odd-degree outside corners available
- Factory-mitered ends available cut to size, including inside/outside corners (real wood models)
- For random lengths, ends to be field-mitered (real wood models)
- Optional vertical accent reveal available for joint between end cap and cover; in black only (Model: FR-225)

# **Certifications/Testing**

- Resistant to certain bacterial & fungal growth (per ASTM G 22-76 & G 21-96)
- Chemical resistant (per ASTM D 543)
- Impact resistant (per ASTM F 476-84)
- UL Class A/1 fire rated & labeled (excludes models FRW-225 & FRW-270N)
- California 01350 Testing (VOC Emissions)



### Acrovyn Finish Options



# **Real Wood Options**





\*Bamboo: available in 7'-8' lengths only. Beech: available in 7'-11' lengths only. For all models.

#### See all finish options online at c-sgroup.com.

### Warranty

• Acrovyn Limited Lifetime Warranty

MODEL	PROFILE	MATERIAL	MAX LENGTH	MOUNT	WALL OFFSET	RAMP TRANSITION	BUY ONLINE
BG-10	4" (101.6mm)	Acrovyn	20' (6.1m)	1/2" (12.7mm) mounting Cushion	2 ‰" (61.9mm)	•	٠
BG-30	2 ¾" (69.9mm)	Acrovyn	20' (6.1m)	1/2" (12.7mm) mounting cushion	1 %" (41.3mm)	•	٠
BL-100	4" (101.6mm)	Acrovyn	20' (6.1m)	1/2" (12.7mm) mounting cushion	2 ¾" (60.3mm)		
BL-200	4" (101.6mm)	Acrovyn	20' (6.1m)	Aluminum bracket assembly	Up to 12" (304.8mm)		
FR-125	1 1⁄8" (28.6mm)	Acrovyn	12' (3.7m)	N/A	1 1⁄8" (28.6mm)		٠
FR-225	2 ¼" (57.2mm)	Acrovyn	20' (6.1m)	N/A	3/4" (19.1mm)		٠
FR-270	2" (50.8mm)	Acrovyn	20' (6.1m)	N/A	1" (25.4mm)		٠
FRW-225	2 ¼" (57.2mm)	Wood	7-12' (2.1-3.7m) varies by species random wood rail length	1" (25.4mm) stainless steel mounting clip	3/4" (19.1mm)		
FRW-270	3 ¾" (95.3mm)	Acrovyn/ Wood	20' (6.1m) Acrovyn rail. Wood rail varies by species	N/A	1 15⁄32" (37.3mm)		

# **Model Details**



Questions? Connect with a CS Representative. c-sgroup.com/representative-locator c-sgroup.com | 800.233.8493 ©2023 Construction Specialties, Inc.