

| Suggested Specifications | Section 10 21 24 Surface Mounted Cubicle Track and Carriers

Part 1 – General

1.01 Summary

- A. Section includes:
 - a. Ceiling mounted curtain track
 - b. Track accessories and attachments

1.02 Submittals

- A. Product Data: Manufacturer's product data sheets for all specified curtain track.
- B. Detail Drawings: Mounting details with the appropriate fasteners for specified project substrates.
- C. Samples: Verification samples of cubicle track, 4" (102mm) in length. Complete with (1) carrier as specified and stop.
- D. Manufacturer's standard installation instructions

1.03 Delivery, Storage, and Handling

- A. Deliver materials in unopened factory packaging.
- B. Inspect material on delivery to verify products are as specified.

1.04 Warranty

- A. Manufacturer's standard warranty against manufacturer defects.

Part 2 - Products

2.01 Acceptable Manufacturers

- A. Subject to compliance with the requirements listed, provide cubicle track and carriers from the following manufacturer:
 - 1. CS Cubicle Curtains
3 Werner Way
Lebanon, NJ 08833
P: (800) 416-1102
CCInfo@c-sgroup.com
www.c-sgroup.com
 - 2. Substitutions: Alternative manufacturers will not be accepted

2.02 Cubicle Track System

- A. Cubicle Tracks: CS Cubicle Curtains #6062N surface-mounted tracks of heavy extruded aluminum alloy 6063-T4, 1 3/8" x 3/4", slotted to receive roller carriers, complete with accessories and components required for complete and secure installations including splices, end caps and corner bends.
 - 1. Corner Bends: Corner bends up to 36" radius are to be fabricated in one continuous "L" shape. Radiuses above 36" to be continuous or spliced based on room condition.
 - i. Finish:
 - <Note to specifier – choose desired track finish>
 - 1. Clear anodized aluminum [OR]
 - 2. White powder coat finish
- B. Carriers:
 - <Note to specifier - choose desired carrier for project (1, 2, 3, 4, or combination of)>
 - 1. CS Cubicle Curtains 1062N, virgin nylon axle with nylon wheels complete with nickel-plated brass bead-chain and hook assembly.
 - i. Provide one carrier for each 6" of cubicle curtain width.
 - 2. CS Cubicle Curtains 975, all nylon carriers. Carrier to have virgin nylon hook, axle and nylon wheels.

- i. Provide one carrier for each 6" of cubicle curtain width.
- 3. CS Cubicle Curtains SP062, spool carrier with all nylon spool, nickel plated brass bead connector, and aluminum hook.
 - i. Provide one carrier for each 6" of cubicle curtain width.
- 4. Breakaway Carriers: CS Cubicle Curtains 975P, all nylon breakaway carriers. Carrier to have virgin nylon hook, axle and nylon wheels. Carrier hook is to be designed to break away from axle at 22 pounds of applied pressure.
 - i. Provide one carrier for each 6" of cubicle curtain width

END OF SECTION