

# Surface Mounted Cubicle Track and Carriers

Suggested Specifications | Section 10 21 24

## Part 1 - General

### 1.01 Summary

- A. Section includes:
  - a. Ceiling mounted curtain track
  - b. Track accessories and attachments

### 1.02 Submittals

- A. Product Data: Manufacturer's product data sheets for all specified curtain track.
- B. Detail Drawings: Mounting details with the appropriate fasteners for specified project substrates.
- C. Samples: Verification samples of cubicle track, 4" (102mm) in length. Complete with (1) carrier as specified and stop.
- D. Manufacturer's standard installation instructions

### 1.03 Delivery, Storage, and Handling

- A. Deliver materials in unopened factory packaging.
- B. Inspect material on delivery to verify products are as specified.

### 1.04 Warranty

- A. Manufacturer's standard warranty against manufacturer defects.

## Part 2 - Products

### 2.01 Acceptable Manufacturers

- A. Subject to compliance with the requirements listed, provide cubicle track and carriers from the following manufacturer:
  - 1. CS Cubicle Curtains  
3 Werner Way  
Lebanon, NJ 08833  
P: (800) 233-8493  
CCInfo@c-sgroup.com  
www.c-sgroup.com
  - 2. Substitutions: Alternative manufacturers will not be accepted

### 2.02 Cubicle Track System

- A. Cubicle Tracks: CS Cubicle Curtains #6063 suspended-mounted tracks of heavy extruded aluminum alloy 6063-T5, 1 3/8" x 3/4", slotted to receive roller carriers, complete with accessories and components required for complete and secure installations including splices, end caps and corner bends.
  - 1. Suspension Height: 3/4" square aluminum hangers with suspension brackets made of molded nylon to adapt to CS 6063 aluminum track.
    - 1. Suspension bar height to be: \_\_\_\_ (insert height of suspension here)

2. Corner Bends: Corner bends up to 36" radius are to be fabricated in one continuous "L" shape. Radiuses above 36" to be continuous or spliced based on room condition.

- i. Finish:

- <\*\*Note to specifier - choose desired track finish>

1. Clear anodized aluminum [OR]
      2. White powder coat finish

- B. Carriers:

- <\*\*Note to specifier - choose desired carrier for project (1, 2, 3, 4, or combination of)>

1. CS Cubicle Curtains 1062N, virgin nylon axle with nylon wheels complete with nickel-plated brass bead-chain and hook assembly.
        - i. Provide one carrier for each 6" of cubicle curtain width.
      2. CS Cubicle Curtains Breakaway Carrier SBC30 designed to pop out on one side when 8 lbs of pressure is applied. Beaded nylon carrier.
        - i. Provide one carrier for each 6" of cubicle curtain width.
      3. CS Cubicle Curtains SP062, spool carrier with all nylon spool, nickel plated brass bead connector, and aluminum hook.
        - i. Provide one carrier for each 6" of cubicle curtain width.
      4. Breakaway Carriers: CS Cubicle Curtains 1075P, all nylon breakaway carriers. Carrier to have virgin nylon hook, axle and nylon wheels. Carrier hook is to be designed to break away from axle at 8 to 10 pounds of applied pressure.
        - i. Provide one carrier for each 6" of cubicle curtain width

END OF SECTION