

## Hookless Shower Curtains

Suggested Specifications | Section 10 21 23

### Part 1 – General

#### 1.01 Related Documents

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 1 Specification Sections, apply to this Section.

#### 1.02 Summary

- A. This section includes the following:
  - 1. Hookless shower curtains

#### 1.03 Performance Requirements

- A. Curtains: Provide curtain fabrics with the following characteristics:
  - 1. Polyester fabrics are launderable at temperatures of 140 degrees F (60 Deg C).
  - 2. CS does not recommend washing vinyl shower curtains in a washing machine. Instead, vinyl curtains should be wiped down with warm, soapy water and then thoroughly rinsed. Allow the curtain to completely air dry before next use (if possible).

#### 1.04 Submittals

- A. Product Data: Submit copies of manufacturer's detailed technical data for materials, fabrication, and physical appearance.
- B. Shop Drawings: Show layout and types of cubicle curtains, sizes of curtains, and number of carriers.
- C. Samples for Verification: Provide samples of the following:
  - 1. Curtain Fabric: 12-inch square swatch or larger sample as required to show complete pattern repeat, from dye lot used for the work, with specified treatments applied.

#### 1.05 Warranty

- A. Provide copy of manufacturer's standard warranty.

### Part 2 - Products

#### 2.01 2.01 Manufacturer

- A. **Basis of Design** - manufactured by Construction Specialties Subject to compliance with the requirements listed, provide cubicle curtains from the following manufacturer:

Construction Specialties, 3 Werner Way, Lebanon, NJ 08833. Tel: 800.233.8493. Email: [cet@c-sgroup.com](mailto:cet@c-sgroup.com) No substitutions.

- B. Drawings and specifications are based on manufacturer's literature from Construction Specialties, Inc. drawings and specifications unless otherwise indicated. Other manufacturers must be approved equal by Architect/Owner.

2.02 Materials

- A. Shower Curtain:
  - 1. Fabric: Fabric to be non-vinyl, and antimicrobial.

2.03 Pattern and Color

<\*\*\*Note to specifier – please select one of the following standard colors for Hookless shower curtains>

- A. Shower Curtain Fabric: Fabric in the following pattern/color:
  - a) Pin Dot (Eight Gauge Vinyl).
    - 1) Color: Beige – Size: 42" x 74"
    - 2) Color: White - Sizes: 71" x 80", 71" x 74" or 42" x 74"
  - b) Litchfield (100% Polyester)
    - 1) Color: White – Sizes: 71" x 74" or 42" x 74"
    - 2) Color: Beige – Sizes: 71" x 74" or 42" x 74"
  - c) Mini-Square (100% Polyester, Fire Retardant, meets NFPA 701)
    - 1) Color: Beige. Sizes: 42" x 74" or 71" x 74"
    - 2) Color: Sage Size: 42" x 74"
  - d) Mystery with Sheer Window (100%Polyester)
    - 1) Color: White – Size: 71" x 74"
    - 2) Color: Beige – Size: 71" x 74"
    - 3) Color: Sage – Size: 71" x 74"

2.04 Fabrication

- A. Shower Curtains to be fabricated as follows:
  - a) Panel Size:
    - 1) 71" x 74"
    - 2) 42" x 74"
    - 3) Custom: \_\_\_\_\_

Part 3 – Execution

3.01 Examination

- A. Examine areas and conditions in which the shower curtain will be installed
  - 1. Complete all finishing operations, including painting, before beginning installation of shower curtain and curtain rod/track materials.
  - 2. Verify that surfaces and above ceiling supports are ready to receive work.

3.02 Cleaning

- A. At completion of the installation, remove any debris and clean surfaces in accordance with CS cleaning and maintenance instructions.

END OF SECTION