## **GTW** Series



Model GTW

This flush, dual-gasket wall and ceiling cover is ideal for interior applications with larger thermal movement requirements. The gasket edges lock into aluminum retainers to prevent hairline gaps and ensure a hygienic seal.

#### **Advantages**

- Flush with construction substrate
- Hygienic
- Corresponding floor and ceiling covers for seamless sightline







Construction Specialties<sup>•</sup>

Questions? Connect with a CS Representative. c-sgroup.com/representative-locator c-sgroup.com | 800.233.8493 ©2023 Construction Specialties, Inc.

# **GTW** Series

### **Product Details**

- Joint sizes range from 2" to 4" (50.8mm to 101.6mm)
- 10' (304.8cm) stock lengths
- Injection molded turnbar
- Self-centering center plate with turnbar
- Meets ASTM E1399



### **Model Details**



MODEL	WALL TO WALL	WALL TO CORNER	NEW TO EXISTING
GTW	•		
GTWC		•	
GTWM			•

### Gasket Color Options





nodize

Aluminum in contact with concrete/masonry will have a 2 mil, heavy metal free, high solids primer

See all finish options online at c-sgroup.com.

### Warranty

• Standard Five-Year Warranty





Construction Specialties

Questions? Connect with a CS Representative. c-sgroup.com/representative-locator c-sgroup.com | 800.233.8493 ©2023 Construction Specialties, Inc.

 $\rightarrow$