

Dutch Doors

Acrovyn® Dutch Doors are designed to be divided horizontally so one part can remain closed while the other is open, providing users both access and privacy as needed. These doors are offered in a variety of finish options and panel designs.

Advantages

- Shelf options available for added functionality
- Various aesthetic options such as paneled designs, help meet any design need
- Unlike square, banded edges, rounded edges offer better protection against impact where most door damage occurs
- Edge covers & stiles are quick and easy to replace on-site if damage occurs
- Durable Acrovyn holds up against daily wear and tear, keeping the doors looking like new
- Customization available to provide extra flexibility to meet specific design needs

Applications

- High-traffic, interior environments with specific requirements regarding access and privacy, such as administrative offices, classrooms, mailrooms, etc.

Building Segments

- Healthcare
- Senior Living
- Education
- Hospitality
- Retail
- Corporate & Commercial
- Civic & Cultural



Dutch Doors

Product Details

- Available up to a 20-minute fire rating
- PVC-free Acrovyn
- 1¾" (44.5mm) door thickness
- Optional single or double-sided shelves available, with or without gussets (max overhang: 6" (152.4mm))
- Prepped for hardware
- Cutouts, vision kits, glazing, & astragals available
- Louvers available on non-rated model only
- Top & bottom rails factory sealed with approved sealant
- Contributes toward LEED v4 credits

Acrovyn Finish Options



- Stainless steel edges available

See all finish options online at [c-sgroup.com](https://www.c-sgroup.com).

Certifications / Testing

- Cycle Slam: Extra Heavy Duty per WDMA TM-7 (tested to 2,000,000 cycles, double the industry standard)
- Resistant to certain bacterial & fungal growth (per ASTM G 22-76 & G 21-96)
- Chemical resistant (per ASTM D543-06)
- Taber abrasion resistant (per ASTM D 4060-07) (suede & shadowgrain textures only)
- Fire test standards: UL-10C, CAN/ULC S104, & NFPA 252 (Fire rated models only)



Model Details

MODEL	WEIGHT	CORE	MAX SIZE SINGLE	MAX SIZE PAIR OR DOUBLE EGRESS	FIRE RATING
DD SCL5-NR	6.87lb/ft ²	Bonded SCL	4'3" (1.3m) x 10'0" (3.0m)	8'6" (2.6m) x 10'0" (3.0m)	Non-rated
DD SCL5-20PP	6.92lb/ft ²	Bonded SCL	4'0" (1.2m) x 8'0" (2.4m)	N/A	20-minute

See Dutch Doors →

