

**Non-Rated Dutch Door (DD SCL5-NR)
Bonded SCL Core, 5-Ply Construction**

	Single Swing	Pair or Double Egress
Core Type & Standards	Structural Composite Lumber: (38 lb/ft3)	
Maximum Sizes	4'3" x 10'0"	8'6" x 10'0"
Protection Plates	Up to 48" (above bottom of door)	
Door Thickness	1-3/4" (+/- 1/16")	
WDMA Prefit Tolerance	Width: (+/- 1/32") Height & Thickness: (+/- 1/16")	
Weight	6.87lb/ft2 (3070 Door = 144lbs) (4070 Door = 193lbs)	
Crossband	High Density FSC Fiberboard	
Blocking	(Standard) Full Core Blocking; 1" Fixed Internal Stiles	
Assembly Adhesive	Face: Type I (waterproof); Core: Type II (water-resistant)	
Replaceable Edge Stiles & Covers	Field Replaceable SCL Stiles. Acrovyn and/or 20GA #4 finish Stainless Steel Replaceable Covers	
Replaceable Edge Profile	Beveled, Square, Radius	
Lites	5" from edges, 1-1/2" from hardware or additional cutouts	
Max Lite Cutout Area	No restrictions	
Lite Frames	Wood beads; Metal – Painted, Wood Veneered, Acrovyn Wrapped	
Glazing	No restrictions	
Louvers	Up to 24" x 24"; 10" From Bottom of Door & 1-1/2" From Hardware or Additional Cutout	
Electronic Options	Electronic hardware & raceways available	
Hinges	Mortised, Surface & Continuous	
Pivots	Center hung & offset w/ intermediate	
Locks	Mortise & Cylindrical	
Exit Devices	Surface Vertical Rod (Includes LBR), RIM & Mortised	
Concealed Vertical Rod	Available (Includes LBR)	
Flushbolts	Must Be Extension Type (Metal Door)	
Closing Devices	Mortised or Surface Mounted	
Door Bottoms	Mortised or Surface Mounted	
Transoms	Available	
Shelf Options	Optional – Single or Double sided, with or without gussets Max shelf overhang – 6 inches	

