

SCR-F Series



Model SCR-48

The SCR-F series of crash rails provide impact resistance with a continuous aluminum retainer or aluminum clips. For additional shock absorption, choose from three mounting options.

Advantages

- Shock absorbing; designed to take impact
- Covers easily replaced
- Multiple aesthetic and functional options available to meet any design requirement
- Flat edge offers a more modern look
- 3 profile sizes available

Building Segments

- Healthcare
- Office & Mixed Use
- Retail
- Hospitality
- Senior Living
- Sports & Entertainment
- Aviation & Transportation

Applications

- Corridors
- Elevator lobbies
- Lobbies
- Mail rooms
- Headwalls



Learn More →

SCR-F Series

Product Details

- PVC-free Acrovyn in shadowgrain texture
- .078" (1.98mm) thick Acrovyn® cover & end caps
- 90- & odd-degree outside corners available
- Lengths up to 20' (6.1mm)
- Factory formed radius (not available with clip models)
- Regrind PETG mounting cushion

Certifications/Testing


- Resistant to certain bacterial & fungal growth (per ASTM G 22-76 & G 21-96)
- Chemical resistant (per ASTM D 543)
- Impact resistant (per ASTM F 476-84)
- UL Class A/1 fire rated & labeled
- California 01350 Testing (VOC Emissions)



Finish Options



Mounting Options



See all finish options online at c-sgroup.com.

Warranty

- Acrovyn Limited Lifetime Warranty

Model Details

MODEL	PROFILE	MOUNT	WALL OFFSET	RAMP TRANSITION	BUY ONLINE
SCR-40	4" (101.6mm)	Surface mounted continuous aluminum retainer	3/4" (19.1mm)	●	●
BCR-40	4" (101.6mm)	1/2" (12.7mm) bumper mounted continuous aluminum retainer	1 3/16" (30.2mm)	●	●
ECR-40	4" (101.6mm)	2 1/8" (54.0mm) mounting bracket continuous aluminum retainer	2 7/8" (73.0mm)	●	●
SCR-48	6" (152.4mm)	Surface mounted 1 1/2" (38.1mm) aluminum clips	1 1/4" (31.8mm)	●	●
SCR-48M	6" (152.4mm)	Surface mounted continuous aluminum retainer	1 1/4" (31.8mm)	●	●
BCR-48	6" (152.4mm)	1/2" (12.7mm) bumper mounted continuous aluminum retainer	1 3/4" (44.5mm)	●	●
ECR-48	6" (152.4mm)	2 1/8" (54.0mm) mounting bracket continuous aluminum retainer	3 7/16" (87.3mm)	●	●
SCR-64	8" (203.2mm)	Surface mounted 1 1/2" (38.1mm) aluminum clips	1 1/4" (31.8mm)	●	●
SCR-64M	8" (203.2mm)	Surface mounted continuous aluminum retainer	1 1/4" (31.8mm)	●	●
BCR-64	8" (203.2mm)	1/2" (12.7mm) bumper mounted continuous aluminum retainer	1 3/4" (44.5mm)	●	●
ECR-64	8" (203.2mm)	2 1/8" (54.0mm) mounting bracket continuous aluminum retainer	3 7/16" (87.3mm)	●	●