AW Series



Featuring a solid wood handrail and crash rail combination, this series offers a wide range of high-end aesthetic options and custom capabilities to meet any design need. Designed for patient safety, these are most suited for behavioral health facilities.

Advantages

- Real wood offers an elevated design in spaces that require a high-end feel
- Custom finishes available to help meet specific design needs
- Factory finished wood handrail, crash rail and endcaps available with low VOC water-based wood finishes
- Acrovyn[®] Quick Lock[™] mounting brackets which cuts down installation time by 50%
- Behavioral health models feature continuous aluminum bracket

Building Segments

- Education
- Healthcare
- Retail & Hospitality
- Senior Living



Learn More



AW Series

Product Details

- Continuous outside corners
- Field-mitered ends standard with optional factoryassembled units available to field-verified dimensions only
- Continuous Aluminum retainer
- Wood Quick Lock mounting standard
- Feature insert available in limited solid colors
- Optional horizontal Acrovyn accent reveal is available for AW-10C in select solid colors
- PVC-free Acrovyn in shadowgrain texture

Certifications/Testing

- ASTM E84 Class A/1 fire
- Low VOC Emissions Certificate Intertek Clean Air Gold (CDPH 01350 v1.2)

Model Insert Options

Add corresponding letter to model number for required insert option:

- Finish grooves (G)
- Feature insert (V)
- Stainless steel (S)

Handrail Bracket Options



Health High Load

Model Details

Acrovyn Finish Options



Real Wood Options

0ak





All woods are available in the following finishes.



*Bamboo: available in 7'-8' lengths only. Beech: available in 7'-11' lengths only. For all models.

Optional Powder Coat Finishes



Feature Insert Colors



See all finish options online at c-sgroup.com.

Warranty

Acrovyn Limited Lifetime Warranty

MODEL	LENGTH MIN-MAX	WALL OFFSET	MODEL FEATURES	RAMP TRANSITION	RADIUS
AW-10C	Min 13" (330.2mm). 7-12' (2.1-3.7m) max wood rail length. Varies by species.	3" (76.2mm)	🛞 Standard Plain Face	•	•
AW-10CCB	Min 13" (330.2mm). 7-12' (2.1-3.7m) max wood rail length. Varies by species.	3" (76.2mm)	Continuous Wooden mounting bracket with Plain Face		
AW-10CCM	Min 13" (330.2mm). 7-12' (2.1-3.7m) max wood rail length. Varies by species.	3" (76.2mm)	(3) (B) Continuous mounting bracket with Plain Face		
AW-10CVB	Min 13" (330.2mm). 7-12' (2.1-3.7m) max wood rail length. Varies by species.	3" (76.2mm) + Vinyl	🛞 Standard with Vinyl Bumper	•	•
AW-10CVBCB	Min 13" (330.2mm). 7-12' (2.1-3.7m) max wood rail length. Varies by species.	3" (76.2mm) + Vinyl	(BH) Continuous mounting bracket with Vinyl Bumper		
AW-10CVBCM	Min 13" (330.2mm). 7-12' (2.1-3.7m) max wood rail length. Varies by species.	3" (76.2mm) + Vinyl	(2) (BH) Continuous mounting bracket with Vinyl Bumper		
AW-LR	Min 12" (304.8mm). 7-12' (2.1-3.7m) max wood rail length. Varies by species.	3 ½" (88.9mm)	Plain Face	•	
AW-LRVB	Min 12" (304.8mm). 7-12' (2.1-3.7m) max wood rail length. Varies by species.	3 ½" (88.9mm)	Vinyl Bumper	•	



Construction Specialties

Questions? Connect with a CS Representative. c-sgroup.com/representative-locator

c-sgroup.com | 800.233.8493 ©2024 Construction Specialties, Inc.