

Disposable Cubicle Curtains – On the Right Track

Suggested Specifications | Section 10 21 23

Part 1 – General

1.01 Related Documents

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 1 Specification Sections, apply to this Section.

1.02 Summary

- A. This section includes the following:
 - 1. Disposable Cubicle curtains

1.03 Performance Requirements

- A. Curtains: Provide curtain fabrics with the following characteristics:
 - 1. Flame retardant, meeting NFPA 701 standards
 - 2. Antimicrobial
 - 3. Fabricated of polypropylene
 - 4. Manufactured with integral (punched) mesh
 - 5. Disposable

1.04 Submittals

- A. Product Data: Submit copies of manufacturer's detailed technical data for materials, fabrication, and physical appearance.
- B. Shop Drawings: Show layout and types of cubicle curtains, sizes of curtains, and number of carriers.
- C. Samples for Verification: Provide samples of the following:
 - 1. Curtain Fabric: 12-inch square swatch or larger sample as required to show complete pattern repeat, from dye lot used for the work, with specified treatments applied.
- D. Cubicle Schedule: Use same room designations as indicated on drawings
- E. Maintenance Data: Provide fabric manufacturer's standard maintenance procedure documentation.

1.05 Project Conditions

- A. Environmental Limitations: Do not install cubicles until spaces are enclosed and weatherproof, wet work in spaces is complete and dry, work above ceilings is complete, and ambient temperature and humidity conditions are maintained at the levels indicated for Project when occupied for its intended use.
- B. Field Measurements: Where cubicles are indicated to fit to other construction, verify dimensions of other construction by field measurements before fabrication and indicate measurements on Shop Drawings. Coordinate fabrication schedule with construction progress

to avoid delaying the work.

1.06 Warranty

- A. Provide copy of manufacturer’s standard warranty.

Part 2 - Products

2.01 Manufacturers

- A. Basis of Design – manufactured by Construction Specialties, Inc. Subject to compliance with the requirements listed, provide cubicle curtains from the following manufacturer:
Construction Specialties, Inc., 3 Werner Way Lebanon, NJ 08833. Tel.: 800.233.8493. Email: cet@c-sgroup.com. No substitutions. www.c-sgroup.com

2.02 Materials

- A. On The Right Track Recyclable Disposable Cubicle Curtains as manufactured by Construction Specialties, Inc.
 - 1. Fabric: Provide 100% polypropylene, disposable fabric with panel, mesh and top designed for attachment to track without separate hooks.

2.03 Pattern and Color

<**Note to specifier – please choose the desired solid color to be used on disposable curtains. Note that a custom print will require a minimum quantity>

- A. Cubicle Curtain Fabric: fabric to be of one of the following solid colors:
 - 1. CSelect Floatstone (Coordinates with CSelect Fabric Pattern Sandstone)
 - i. Eddy
 - ii. Sunrise
 - 2. CSelect Pattern Turtlegrass (Coordinates with CSelect Fabric Pattern Seagrass)
 - i. Tides
 - ii. Tidal Pool
 - 3. Boxed Leaf Pattern
 - 4. Ivy Pattern
 - 5. Silver Cottonwood
 - 6. Magic Waves
 - 7. Migration
 - 8. Trellis
 - 9. Trellis Gray
 - 10. Echo
 - 11. Landscape
 - 12. Custom: _____

2.04 Fabrication

- A. Disposable Cubicle Curtain with the following characteristics:
 - 1. Available Panel sizes: 69”x 82” (1.8m x 2.1m), 69”x92” (1.8m x 2.3m) or 69”x110” (1.8m x 2.8m)

high including 19 inches of mesh, hemmed as required.

2. Curtain Loading Tool: Manufacturer's standard loading tool, The Grabber
3. Curtain Ring Color:
 - a. Cream

Part 3 – Execution

3.01 Examination

- A. Examine areas and conditions in which the cubicle track system will be installed
 1. Complete all finishing operations, including painting, before beginning installation of cubicle tracking system materials.
 2. Verify that surfaces and above ceiling supports are ready to receive work.

3.02 Installation

- A. General: Locate the cubicle track as indicated on the approved detail drawing for the appropriate substrate
- B. Installation of Cubicle Track System:
 1. Install On The Right Track cubicle curtain track, secure, rigid, and true to ceiling line.
 2. Secure or suspend track to ceiling system. Install with mechanical fasteners or T-Grid clips.
 3. Install curtains on carriers ensuring smooth operation.

END OF SECTION