

OPENING		PROJECT		CS Construction Specialties®					
SINGLE _____ * AVAILABLE ONLY AS SINGLES		CUSTOMER	DATE	QUOTE #					
DUTCH DOOR SIZING (HEIGHT)		FRAME OPENING SIZE (WIDTH X HEIGHT)		PREFIT DOOR SIZE (WIDTH X HEIGHT)					
UPPER LEAF: HEIGHT = _____ * ASSUMES 1/8" TOP GAP & 1/8" GAP BETWEEN LEAFS				BLOCKING N/A, SCL CORE					
FIRE RATING NR OR 20* "S" Label? Y N * 20min LABEL: EACH LEAF MUST LATCH INTO THE FRAME				DOOR FACE ACROVYN COLOR # DOOR EDGE ACROVYN COLOR #					
LITE VISIBLE GLASS (W x H) _____ OR CUTOUT ONLY (W x H) _____ DISTANCE FROM TOP RAIL (in) _____ DISTANCE FROM LOCK STILE (in) _____ -OR- CHECK IF CENTERED LIGHT KIT TYPE (IF TO BE PROVIDED BY CS) NONE: _____ METAL: PAINTED TO MATCH _____ METAL: BEIGE (PC) _____ WOOD: FLUSH BEAD _____ METAL: ACROVYN WRAPPED _____ WOOD: LIPPED BEAD _____									
GLASS OPTIONS (CHECK REQUIRED OPTION) NONE 1/4" TEMPERED (NR) 1/4" FIREGLASS 20 (20) 1/4" SUPERLITE I (20) 1/4" SUPERLITE I-W (20) 3/16" FIRELITE NT (20) 5/16" FIRELITE PLUS (20) OTHER _____ SUPPLIED BY OTHERS? Y N INSTALLED BY CS? Y N									
NOTES		HINGE (*REQUIRED FOR FABRICATION) MANUFACTURER* _____ MFG. MODEL NO.* _____ SIZE (HEIGHT x THICKNESS)* _____ TEMPLATE NO.* _____		EDGE TYPE: HINGE: ☐ BEVELED ☐ SQUARE ☐ RADIUS LATCH: ☐ BEVELED ☐ SQUARE ☐ RADIUS		LOCKSET (*REQUIRED FOR FABRICATION) MANUFACTURER* _____ MFG. MODEL NO.* _____ CYLINDRICAL* MORTISE* _____ TEMPLATE NO.* _____		CONCEALED CLOSER / STOP (DEGREE OF OPENING, MFG., MODEL & TEMPLATE NO.) _____ EXIT DEVICE (MFG., MODEL & TEMPLATE NO.) _____ DEAD BOLT (MFG., MODEL & TEMPLATE NO.) _____ DOOR BOTTOM (MFG., MODEL & TEMPLATE NO.) _____ MISC. HARDWARE (TYPE, MFG., MODEL, & TEMPLATE NO.) _____ DUTCH DOOR HARDWARE (TYPE, MFG., MODEL, & TEMPLATE NO.) _____	
PAGE _____ OF _____									