

OMPOSITE PANELS

Building Materials Structural, Industrial or Decorative



Safety Data Sheet

Particleboard

Section 1: Identification

Product Name

Particleboard

Synonyms

• UPine, Duraflake, Rezflake, Vesta PB

This SDS is applicable for standard Arauco North America particleboard manufactured at the sites noted below including specialty products such as moisture-resistant (MR), panels manufactured with ultra-low emitting resins (branded Vesta), and panels laminated with thermally fused

laminate (TFL)/melamine.

Product Description Recommended use

• A wood product composed of wood and cured amino resins

• Building Materials - Decorative, Furniture, General Construction

Manufacturing Sites

 Albany, OR Bennettsville, SC St. Stephen, NB

Supplier

ARAUCO North America

5901-B Peachtree Dunwoody Rd NE, Suite 500

Atlanta, GA 30328

USA

http://www.arauco-na.com/

Telephone (General)

• 800-261-4890

Regional Support Centers

• Canadian Regional Center

80 Tiverton Court, Suite 701 Markham L3R 0G4

Canada

Tel: (905) 475-9686 Fax: (905) 475-3827

US Western Regional Center

2550 NE Old Salem Road

Albany, OR 97321 Tel: (888) 650-6302 Fax: (541) 928- 4116 **US Eastern Regional Center**

515 River Crossing Drive,

Suite 110

Fort Mill, SC 29715

Tel: (877) 273-7680 Fax: (800) 808-1454



MPOSITE PANELS

Building Materials Structural, Industrial or Decorative



Section 2: Hazard Identification

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

OSHA HCS 2012

This product is generally an article but is regulated under OSHA for the release
of wood dust during mechanical operations releasing dust. The free
formaldehyde levels are below OSHA reporting requirements. The classifications
below are based upon wood dust.

Skin Irritation 2 Skin Sensitization 1 Eye Mild Irritation 2B Respiratory Sensitization 1

Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation

Carcinogenicity 1A Combustible Dust

Label elements OSHA HCS 2012

DANGER





Hazard statements • Causes skin irritation

May cause an allergic skin reaction

Causes eye irritation

May cause respiratory irritation

May cause allergy or asthma symptoms or breathing difficulties if inhaled

May cause cancer via inhalation of respirable dust May form combustible dust concentrations in air.

Precautionary statements

Prevention • Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust.

Contaminated work clothing should not be allowed out of the workplace.

In case of inadequate ventilation wear respiratory protection.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection.

Response • IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Building Materials Structural Industrial or Decorative





IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

IF exposed or concerned: Get medical advice/attention.

Storage/Disposal • Store away from water and ignition sources. It is recommended to store the product in an area with relative humidity and temperature that approximates end

> Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Other hazards

OSHA HCS 2012

 This product is not considered hazardous under the U.S. OSHA 29 CFR 1910.1200 Hazard Communication Standard.

Other information

NFPA •Health = 1, Flammability = 1, Reactivity = 0, Special Information = None

HMIS • Health = *1, Flammability = 1, Reactivity = 0, PPE = E

* Chronic Health Hazard

E = Safety glasses, gloves, and a dust respirator

Section 3 - Composition/Information on Ingredients

Mixtures

These wood products are composed of wood and cured amino resins. See Section 8 for exposure limits discussion.

Components shown below may appear in some or in various combinations in a particular product. With the exception of Formaldehyde, only hazardous components above the appropriate cut-off limit are shown.

Composition				
Chemical Name	Identifiers	%	Hazardous	
Wood fibers *	CAS: Not Available	83% TO 92%	Yes	
Cured amino resins	CAS: Proprietary	0% TO 17%	Yes	
Cured amino resins	CAS: Proprietary	0% TO 15%	No	
Urea	CAS: 57-13-6	0% TO 2%	Yes	
Formaldehyde	CAS: 50-00-0	<0.1%	Yes	

^{*} Wood contains trace amounts of various chemicals present in the environment which are absorbed by trees through natural growth. A comprehensive listing of species is available upon request.

All products produced at Arauco NA mills are certified to the Composite Panel Association's Eco-certified Composite (ECC) Sustainability Standard which requires adherence to the strict California Air Resources Board (CARB) Composite Wood Formaldehyde Air Toxic Control Measure (CARB ATCM 93120.12).

CALIFORNIA RESIDENTS: This product contains one or more chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

Section 4: First-Aid Measures

Description of first aid measures

Inhalation • IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.



Building Materials Structural Industrial or Decorative



ARAUCO. Growing the Future

Skin

• IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Eye

• IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion • Health effects are not known or expected to occur under normal use. Low hazard for usual industrial or commercial handling.

Most important symptoms and effects, both acute and delayed

• Refer to Section 11 - Toxicological Information.

Section 5: Fire-Fighting Measures

Extinguishing media

Suitable Extinguishing Media

• SMALL FIRES: Dry chemical, CO2, water spray or regular foam. LARGE FIRE: Water spray, fog or regular foam.

Unsuitable Extinguishing Media

• No data available

Firefighting Procedures

• No special procedures. Fire-fighting procedures for wood products are well known.

Special hazards arising from the substance or mixture

Hazards

- Unusual Fire and Explosion Particleboard is not an explosion hazard. Sawing, sanding, or machining particleboard could result in the by-product wood dust. Wood dust may present a strong to severe explosion hazard if a dust cloud contacts an ignition source.
 - Airborne concentrations of 40 grams per cubic meter are often used as the lower explosive limit (LEL) for wood dusts. OSHA interprets the explosive level as having no visibility within five feet or less.

Hazardous Combustion Products

 Burning of particleboard can result in carbon dioxide, carbon monoxide, oxides of nitrogen, aldehydes, cyanides and other hazardous gases and particles.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Do not breathe dust.

Emergency Procedures

 No emergency procedures are expected to be necessary if material is used under ordinary conditions as recommended.

Environmental precautions

• No known significant environmental effects.

Methods and material for containment and cleaning up

Containment/Clean-up **Measures**

 Not applicable for product in purchased form. Dust generated from sawing, sanding, drilling or routing this product may be vacuumed or shoveled for recovery or disposal. Wood dust clean-up and disposal activities should be accomplished in a manner to minimize creation of airborne dust.



Building Materials Structural Industrial or Decorative



Section 7 - Handling and Storage

Precautions for safe handling

Handling

• No special precautions for handling product. Use good safety and industrial hygiene practices. Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces.

Conditions for safe storage, including any incompatibilities

Storage

 Avoid storage where exposure to water could occur or near a source of ignition. It is recommended to store the product in an area with relative humidity and temperature that approximates end use conditions. Keep away from sources of ignition - No Smoking.

Incompatible Materials • Keep away from ignition sources. or Ignition Sources

Section 8 - Exposure Controls/Personal Protection

Control parameters

Exposure Limits/Guidelines • No data available.

Exposure Limits/Guidelines					
	Result	ACGIH	NIOSH	OSHA	
Wood dust	TWAs	1 mg/m3 TWA as Wood dust, all soft and hard woods	1 mg/m3 TWA as Wood dust, all soft and hard woods	15 mg/m3, total dust (5 mg/m3, respirable fraction) (as nuisance dust)	
Formaldehyde (50-00-0)	TWAs	0.3 ppm STEL	0.016 ppm TWA	0.75 ppm TWA	

Exposure controls

Engineering Measures/Controls Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Due to the explosive potential of wood dust when suspended in air, precautions should be taken during sanding, sawing or machining of wood products to prevent sparks or other ignition sources in ventilation equipment. Use of totally enclosed motors is recommended.

Personal Protective Equipment

Pictograms







Respiratory

 Use of a NIOSH/MSHA approved dust respirator is recommended where airborne dust levels exceed appropriate PELs and TLVs.

Eve/Face

· Wear safety glasses.

Hands

Wear protective gloves - Rubberized cloth, canvas or leather gloves.

Skin/Body

Wear long sleeves and/or protective coveralls.

General Industrial

Hygiene **Considerations** Practice good housekeeping and avoid creating/breathing dust. Do not allow dust to collect. Maintain, clean, and fit test respirators in accordance with OSHA regulations.

Environmental Exposure Controls

No data available



OMPOSITE PANELS

Building Materials Structural, Industrial or Decorative





Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description			
Physical Form	Solid A panel product manufactured from wood fibers bonded with synthetic resins or other bonding system	Appearance/Description	Particleboard panel.
Color	Straw yellow (light brown)	Odor	No distinctive odor.
Taste	No data available.	Odor Threshold	Not relevant
General Properties	•		•
Boiling Point	Not relevant	Melting Point	Not relevant
Decomposition Temperature	No data available	рН	Not relevant
Specific Gravity/Relative Density	Not relevant	Density	No data available
Bulk Density	No data available	Water Solubility	Insoluble
Viscosity	No data available	Explosive Properties	No data available
Oxidizing Properties: No data available			
Volatility	•		
Vapor Pressure	Not relevant	Vapor Density	No data available
Evaporation Rate Not relevant		VOC (Vol.)	0 %
Flammability	•		
Flash Point	Not relevant	UEL	Not relevant
LEL	Not relevant	Burning Time	No data available
Autoignition	425 to 475 F(218.3 to 246.1 C)	Flammability (solid, gas)	No data available

Section 10: Stability and Reactivity

Reactivity

• The product is stable.

Chemical stability

Stable

Possibility of hazardous reactions

• Hazardous polymerization not indicated. Hazardous polymerization will not occur.

Conditions to avoid

• Exposure to water, ignition source, high relative humidity and high temperature.

Incompatible materials

• Incompatible Materials: Acids (strong), Oxidizers (strong)

Hazardous decomposition products

• Hazardous decomposition may occur Thermal and/or thermal oxidative decomposition can produce irritating and toxic fumes and gases, generating carbon oxides, nitrogen oxides, HCN, aldehydes and organic acids.

COMPOSITE PANELS

Building Materials Structural, Industrial or Decorative





Section 11 - Toxicological Information

Information on toxicological effects

Other Material Information

• Not applicable for product in purchased form. Individual component information is provided below if available.

	Components				
Cured Amino Resin	Proprietary	Acute Toxicity: Ingestion/Oral-Rat LD50 • 8394 mg/kg; Inhalation-Rat LC50 • >167 mg/m³ 4 Hour(s); Irritation: Eye-Rabbit • 100 μL 24 Hour(s) • Severe irritation; Skin-Rabbit • 500 mg 24 Hour(s) • Severe irritation			
Formaldehyde	50-00-0	Acute Toxicity: Ingestion/Oral-Rat LD50 • 100 mg/kg; Inhalation-Rat LC50 • 203 mg/m³; Peripheral Nerve and Sensation:Spastic paralysis with or without sensory change; Behavioral:Convulsions or effect on seizure threshold; Behavioral:Excitement; Irritation: Eye-Rabbit • 750 μg 24 Hour(s) • Severe irritation; Skin-Rabbit • 2 mg 24 Hour(s) • Severe irritation; Multi-dose Toxicity: Ingestion/Oral-Rat TDLo • 500 mg/kg 20 Day(s)-Intermittent; Biochemical:Enzyme inhibition, induction, or change in blood or tissue levels:Transaminases; Inhalation-Mouse TCLo • 400 ppb 12 Week(s)-Intermittent; Lungs, Thorax, or Respiration:Other changes; Endocrine:Changes in spleen weight; Biochemical:Metabolism (intermediary):Other proteins; Mutagen: Micronucleus test • Inhalation-Human • 2 ppm 15 Minute(s); Micronucleus test • Inhalation-Human • 0.1 ppm 8 Hour(s); Reproductive: Inhalation-Rat TCLo • 12 μg/m³ 24 Hour(s)(15D pre/1-22D preg); Reproductive Effects:Effects on Newborn:Growth statistics (e.g., reduced weight gain); Reproductive Effects:Effects on Newborn:Other postnatal measures or effects			

GHS Properties	Classification	
Acute toxicity	OSHA HCS 2012•Acute Toxicity - Data lacking (Oral, dermal, inhalation)	
Aspiration Hazard	OSHA HCS 2012•Data lacking	
Carcinogenicity	OSHA HCS 2012•Carcinogenicity 1A	
Germ Cell Mutagenicity	OSHA HCS 2012•Data lacking	
Skin corrosion/Irritation	OSHA HCS 2012•Skin Irritation 2	
Skin sensitization	OSHA HCS 2012•Skin Sensitizer 1	
STOT-RE	OSHA HCS 2012•Specific Target Organ Toxicity Repeated Exposure 2	
STOT-SE	OSHA HCS 2012•Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation	
Toxicity for Reproduction	OSHA HCS 2012•Data lacking	
Respiratory sensitization	OSHA HCS 2012•Respiratory Sensitizer 1	
Serious eye damage/Irritation OSHA HCS 2012•Eye Mild Irritation 2B		

Target Organs

• Skin/Dermal, Lungs, Respiratory System

Route(s) of entry/exposure

• Inhalation, Skin, Eye

Medical Conditions

• Dusts may aggravate asthma or other respiratory disorders.

Aggravated by Exposure

Potential Health Effects

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs include:

Inhalation



Building Materials Structural

8 of 13 Industrial or Decorative



Acute (Immediate)

• May cause respiratory irritation.

Chronic (Delayed)

 Repeated and prolonged exposure may cause cancer. Repeated and prolonged exposure may cause sensitization of the respiratory system.

Skin

Acute (Immediate)

May cause irritation.

Chronic (Delayed)

Repeated and prolonged exposure may cause sensitization.

Eye

Acute (Immediate)

• May cause irritation.

Chronic (Delayed)

No data available.

Ingestion

Acute (Immediate) **Chronic (Delayed)**

• Under normal conditions of use, no health effects are expected.

• Under normal conditions of use, no health effects are expected.

Carcinogenic Effects

 Wood dust is listed by NTP known to be a Human Carcinogen (10th Report), IARC Monographs: Wood dust, Group 1 - IARC Group 1: Carcinogenic to humans; sufficient evidence of carcinogenicity. This classification is primarily based on studies showing an association between occupational exposure to wood dust and adenocarcinoma of the nasal cavities and paranasal sinuses. IARC did not find sufficient evidence of an association between occupational exposure to wood dust and cancers of the hypopharynx, oropharynx, lymphatic and hematopoietic systems, lungs, stomach, colon or rectum.

Carcinogenic Effects					
	CAS	OSHA	IARC	NTP	
Wood dust as Wood dust, all soft and hard woods	Not Available	Not Listed	Group 1-Carcinogenic	Known Human Carcinogen	
Formaldehyde	50-00-0	Specifically Regulated Carcinogen	Group 1-Carcinogenic	Known Human Carcinogen	

Section 12 - Ecological Information

Toxicity

 No information available at this time. As with all foreign substances do not allow to enter the storm drainage systems. These wood products are not expected to pose an ecological hazard as a result of their intended use.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in Soil

No data available

OMPOSITE PANIELS

Building Materials Structural, Industrial or Decorative





Section 13 - Disposal Considerations

Waste treatment methods

Product waste

Burn in a municipal incinerator. Dispose of in an approved landfill. Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste • No data available.

Section 14 - Transport Information					
	UN number	UN proper shipping name	Transport hazard class(es)	Packing group	Environmental hazards
DOT	No Data Available	No Data Available	No Data Available	No Data Available	No Data Available
TDG	No Data Available	No Data Available	No Data Available	No Data Available	No Data Available

Special precautions for user

No special precautions.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

• No data available

Other information

DOT • Not regulated as a hazardous material.

TDG • Not regulated as a dangerous good.

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the mixture

SARA Hazard Classifications

· Acute, Chronic

Inventory				
Component	CAS	Canada DSL	TSCA	
Particleboard	Not Applicable	Not listed. All components are on the Canada DSL or are excluded from listing.	Not listed. All components are on the TSCA inventory or are excluded from listing.	

Canada

Labor

Canada - WHMIS - Classifications of Substances

•Particleboard and ingredients (unless listed below)	N/A	Not listed or below de minimis reporting quantities
		A, B1, D1A, D2A, D2B; B3,
-Formaldahyda	50-00-0	D1A, D2A, D2B, E
•Formaldehyde	50-00-0	(regulated under Formol)

Canada - WHMIS - Ingredient Disclosure List

· Particleboard and ingredients (unless listed below)

N/A Not listed or below de minimis reporting quantities

Building Materials Structural, Industrial or Decorative



ARAUCO. Growing the Future

0.1% (concentration in 50-00-0 Formaldehyde product is below de minimis)

United States

Labor

U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals

· Particleboard and ingredients (unless listed below) N/A Not Listed 50-00-0 1000 lb TQ Formaldehyde

Environment

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

· Particleboard and ingredients (unless listed below) N/A Not Listed 100 lb final RQ; 45.4 kg final Formaldehyde 50-00-0

U.S. - CERCLA/SARA - Section 304 Extremely Hazardous Substances EPCRA RQs

· Particleboard and ingredients (unless listed below) N/A Not Listed •Formaldehyde 50-00-0 100 lb EPCRA RQ

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA TPQs

· Particleboard and ingredients (unless listed below) N/A Not Listed 50-00-0 500 lb TPQ Formaldehyde

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

· Particleboard and ingredients (unless listed below) N/A Not Listed

0.1% de minimis

 Formaldehyde 50-00-0 concentration (concentration

in product is below de

carcinogen, initial date

minimis)

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

· Particleboard and ingredients (unless listed below) N/A Not Listed

 Formaldehyde 50-00-0 1/1/88 (gas)

carcinogen, initial date ·Wood dust as Wood dust, all soft and hard woods N/A 12/18/09

Section 16 - Other Information

Classification method for mixtures

 Carcinogenicity classification based upon cut-off values/concentration limits of ingredients.

Last Revision Date

• February 7, 2014

Preparation Date

• May 27, 2015

Liability

Disclaimer/Statement of • The information contained in this Safety Data Sheet is based on the experience of occupational health and safety professionals and comes from sources believed to be accurate or otherwise technically correct. It is the user's responsibility to determine if the product is suitable for its proposed application(s) and to follow necessary safety precautions. The user has the responsibility to make sure that this sheet is the most up-todate issue.

ARAUCO North America

Safety Data Sheet COMPOSITE PANELS Building A

Building Materials Structural, Industrial or Decorative





• Arauco North America is a trade name used by Flakeboard Company Limited, Flakeboard America Limited, Arauco Panels USA LLC, and other North America affiliates, each of which is an independent company and is not liable or responsible for acts or obligations of its affiliates.



COMPOSITE PANELS

Building Materials Structural, Industrial or Decorative



GHS Product Hazard Label

Particleboard

According to OSHA 29 CFR 1910.1200 HCS





DANGER

This product is generally an article but is regulated under OSHA for the release of wood dust during mechanical operations releasing wood dust. No adverse health effects are expected if the product is handled in accordance with the product label and the product Safety Data Sheet. Symptoms or effects that may arise if the product is mishandled and overexposure occurs include:

Causes skin irritation.

May cause an allergic skin reaction.

Causes eye irritation.

May cause respiratory irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause cancer via inhalation of respirable dust.

May form combustible dust concentrations in air.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust.

Contaminated work clothing should not be allowed out of the workplace.

In case of inadequate ventilation wear respiratory protection.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

IF exposed or concerned: Get medical advice/attention.

Store away from water and sources of ignition. It is recommended to store the product in an area with relative humidity and temperature that approximates end use conditions.

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.



COMPOSITE PANELS

Building Materials Structural, Industrial or Decorative





California Proposition 65 Notification Requirement

Warning

Drilling, sawing, or machining wood products generates wood dust, a substance known to the State of California to cause cancer. Avoid inhaling wood dust or use a dust mask or other safeguards for personal protection.

ARAUCO North America, 5901-B Peachtree Dunwoody Rd NE, Suite 500 Atlanta, GA 30328 General Information: 800-261-4890