




SW-HE-QR24/6.0

LED Strips - Static White High Efficacy



• Field-cutttable up to 192"

1	2	3	4	5	6	7	8
V/WATTS	RATED	CCT - LUMENS/CRI	CONNECTOR/WIRE IN	CONNECTOR/WIRE OUT	WIRE COLOR	WIRE TYPE	ILLUMINATED LENGTH
SW-HE-QR24/6.0	DRY	30					

Sample Part Number: SW-HE-QR24/6.0-DRY-30-BW-CLS-WH-CL2-48"

1	V/WATTS		2	RATED		3	CCT - LUMENS/CRI		4	CONNECTOR/WIRE IN		5	CONNECTOR/WIRE OUT	
SW-HE-QR24/6.0			DRY IP20			30 3000K 682/98			BW Bare Wire (Standard 24") BRL Barrel CON6 Connector 6" CON24 Connector 24"			BW Bare Wire (Standard 24") BRL Barrel CON6 Connector 6" CON24 Connector 24"		
Voltage: 24VDC Wattage: 6.0W/ft									Connector/Wire In not needed to specify product. Typical selection is BW. BW: Standard length is 24", Max length is 120". Request custom length by writing in part number next to BW (example: BW48)			Connector/Wire Out not needed to specify product. Typical selection is CLS or BW. BW: Standard length is 24". Max length is 120". Request custom length by writing in part number next to BW (example: BW48)		
See following pages for compatible power supplies.														

6	WIRE COLOR		7	WIRE TYPE		8	ILLUMINATED LENGTH	
WH White BK Black N/A Specify for Barrel		CL2 Class 2 CL2P Class 2 Plenum Rated N/A Specify for Barrel		2"-192"		2" increments		
Barrel is white		CL2P only available with bare wire leads (BW)						

5 year warranty | Warranty only valid with QTL power supplies | Field modifications must comply with QTL’s installation methods otherwise warranty is null & void | All data has +/- 5% tolerance | UL Listed



SW-HE-QR24/6.0

LED Strips - Static White High Efficacy


3 CCT – LUMENS/CRI - DELIVERED LUMENS

[Calculated L70 = 66000 hrs]
Tested with SW-HE-QR24/6.0-DRY

CCT	Lumen/ft	Luminous Efficacy	CRI Ra	CRI R9	TM30 Rf	TM30 Rg
3000K	682	118	97.6	98.5	93.2	100.3

PHOTOMETRIC PERFORMANCE

Nominal beam spread shown, beam spread varies based on light engine.



4 / 5 CONNECTOR/WIRE – IN/OUT

Connector/Wire In or Out not needed to specify product. Standard configuration is BW for Wire In and CLS for Wire out

BW

.10"

Bare Wire 24"
Stranded 22 AWG

BRL

1.44"
.42"
1.74"
.35"

Barrel 6" - DRY/DMP I
22 AWG

CON6/CON24

1.63"
.38"
1.34"
.39"

6" or 24" Overall
Wire Connector I 22 AWG
IP67 Rated, UL Listed

6 WIRE COLOR

White

Black



SW-HE-QR24/6.0

LED Strips - Static White High Efficacy

COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

DIM TO LEVEL	INDOOR	OUTDOOR
	SW24/5.0, SW-HE, SW-HE+	SW24/5.0, SW-HE, SW-HE+
Dim to Black	Q6M-DC+CAP QTM-DC+CAP iQ-PH iQ-PH+QD1	QOM-DC+CAP QOM-PH
0.1%	QT-CAB-QZ-PH/0-10V QT-CAB-eLED+0-10V QT-CAB-eLED+0-10V-AWN QT-CAB-eLED-ND QTM-eLED+0-10V QTM-eLED-AWN QZ-DMX QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP	Q-SET-QZ-DMX Q-SET-QZ-PH/0-10V Q-SET-eLED+0-10V QOM-eLED+0-10V QZ-DMX QZ-PH/0-10V
1%	QT-CAB-eLED+DALI-DT6 QT-CAB-eLED+DALI-DT6-AWN QTM-eLED(E) QTM-eLED+DALI-DT6 QTM-eLED+DALI-DT6-AWN QZ-DALI-DT6	Q-SET+QZ-DALI-DT6 QOM-eLED+DALI-DT6
10%	Non-Dim Power Supply with SW App Dongle	

DIMMING PROTOCOL	INDOOR	OUTDOOR
	SW24/5.0, SW-HE, SW-HE+	SW24/5.0, SW-HE, SW-HE+
Non-Dim	QTM-eLED+CAP QTM-eLED-ND QZ-ND	Q-SET-QZ-ND Q-SET-eLED-ND QOM-eLED-ND QZ-ND iQ-ND-50-65
Phase	Q6M-DC+CAP QT-CAB-QZ-PH/0-10V QTM-DC+CAP QTM-eLED(E) QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP iQ-PH iQ-PH+QD1	Q-SET-QZ-PH/0-10V QOM-DC+CAP QOM-PH QZ-PH/0-10V
0-10V	QT-CAB-QZ-PH/0-10V QT-CAB-eLED+0-10V QT-CAB-eLED+0-10V-AWN QT-CAB-eLED-ND QTM-eLED+0-10V QTM-eLED-AWN QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP	Q-SET-QZ-PH/0-10V Q-SET-eLED+0-10V QOM-eLED+0-10V QZ-PH/0-10V
Lutron Athena	QT-CAB-eLED+0-10V-AWN QT-CAB-eLED+DALI-DT6-AWN QTM-eLED+DALI-DT6-AWN QTM-eLED-AWN	
ECO System	QTM-eLED(E)	
DMX	QZ-DMX	Q-SET-QZ-DMX QZ-DMX
DALI-2: DT6	QT-CAB-eLED+DALI-DT6 QT-CAB-eLED+DALI-DT6-AWN QTM-eLED+DALI-DT6 QTM-eLED+DALI-DT6-AWN QZ-DALI-DT6	Q-SET+QZ-DALI-DT6 QOM-eLED+DALI-DT6
SCENE App Dimmed	Non-Dim Power Supply with SW App Dongle	



SW-HE-QR24/6.0

LED Strips - Static White High Efficacy

COMPATIBLE WIRING ACCESSORIES

Q-mini-J  UL Listed, miniature junction box, DRY/DMP (WET rated with silicone)	BARREL-EXT  8ft barrel cable extender DRY ONLY	BARREL FOUR-FER  Splits lead from one to four LED Barrel connector fixtures, DRY/DMP	CON120-EXT  10ft Con cable extender DRY/DMP/WET	CON FOUR-FER  Splits lead from one to four LED Con connectors DRY/DMP/WET	CON M - BARREL F  Male con to barrel cable adaptor DRY/DMP
---	--	--	---	---	--

COMPATIBLE CONTROL ACCESSORIES

SCENE APP DONGLE  Wi-Fi or Bluetooth Connectivity

COMPATIBLE APPS

SCENE APP  Create and control scenes and automations
--