ZBSM Series



This surface mounted parking cover has an EPDM seal that allows for movement, while the integral nosing eliminates the need for elastomeric concrete. During installation, the cover is bonded into a high-strength epoxy bedding and is sealed on each side with a urethane sealant, resulting in a durable and watertight system.

Advantages

- ADA compliant wings are smooth and quiet
- Great for parking structures and stadium applications
- Eliminates the need for messy elastomeric concrete
- No mechanical fasteners
- Durable, watertight system
- Splice kits available for field splicing of material







Construction Specialties

Questions? Connect with a CS Representative. c-sgroup.com/representative-locator c-sgroup.com | 800.233.8493 ©2024 Construction Specialties, Inc.

ZBSM Series

Product Details

- Joint sizes range from 1" to 4" (25.4mm to 101.6mm)
- Available in five standard roll sizes: 20', 30', 65', 130' and 200'
- 3,000 lbs. concentrated load per IBC2009 1607.1
- Meets ASTM E1399



Model Details





Aluminum in contact with concrete/masonry will have a 2 mil heavy metal free high solids primer

Warranty

• Standard Five-Year Warrant



MODEL	FLOOR TO FLOOR	FLOOR TO WALL
ZBSM	•	
ZBSM-Alt-1		•





CS

Construction Specialties

Questions? Connect with a CS Representative. c-sgroup.com/representative-locator c-sgroup.com | 800.233.8493 ©2024 Construction Specialties, Inc.

 \rightarrow