COLOR: .375 COLOR TO BE SELECTED FROM ONE OF C/S [9.5mm] .375 STANDARD COLORS. .375 [9.5mm] [9.5mm] INSIDE CORNER **OUTSIDE CORNER** (25N032XXX) (25N035XXX) NO. REQ'D: NO. REQ'D: .375 [9.5mm] .375 CEILING HEIGHT [9.525mm] ``H" JOINT MOLDING (25N033XXX) NO. REQ'D: WAINSCOT TRIM (25N036XXX) NO. REQ'D: UNLESS OTHERWISE NOTED, WAINSCOT COVERING TO BE INSTALLED WITH "ACROVYN INTERIORS **GENERAL NOTES:** MOLDING WATER BASED MASTIC" AND 1) STANDARD SHEET SIZES: 4'x8' OR 4'x10' "SEALING PRIMER" 2) .060 ACROVYN WALL COVER IS SUPPLIED WITH A STANDARD SUEDE TEXTURE. .060 ACROVYN 3) ALL TRIM MEMBERS SHALL BE SUPPLIED IN HIGH IMPACT WALL COVERING VINYL/ACRYLIC ALLOY IN 10' LENGTHS. 4) TO INSURE PROPER INSTALLATION OF .040 ACROVYN WAINSCOT HEIGHT COVERING, USE INSTALLATION SHEETS INCLUDED WITH EACH HARDWARE SHIPMENT. BASE (BY OTHERS) 5) COLOR SELECTION MUST BE INCLUDED WITH THE APPROVED DRAWINGS TO PREVENT ANY DELAYS IN THE 2" FOR FIELD SHIPMENT OF MATERIALS. VARIATION 6) .060 ACROVYN WALL COVER IS AVAILABLE IN ANY OF C/S 64 STANDARD COLORS. INSTALLATION NOTES: MATERIAL TO BE SUPPLIED IN 4'x8' OR 4'x10' SHEETS 1) WAINSCOT TRIM QUANITY IS CALCULATED FOR WAINSCOT NO. 4'x 8' SHEETS REQ'D. (25S001XXX): USE ONLY. NOT FOR EDGE TRIM. NO. 4'x 10' SHEETS REQ'D. (25S018XXX): 2) INSIDE CORNER TRIM QUANITY IS BASE ON WHERE .060 ACROVYN SHEET IS ON ADJOINING WALLS 3) OUTSIDE CORNER TRIM QUANITY IS BASED ON SHEET AT PARTIAL HEIGHT ON BOTH WALLS AT CORNER. PROJECT: REV. LOCATION: F&F Construction Specialties* **CUSTOMER:** SHEET OF 6696 Route 405 Highway, Muncy PA 17756 (800) 233-8493 Fax (570) 546-4692 www.c-sgroup.com

AGENT:

DWG. BY:

DATE:

JOB NO.