


CHANNEL GUARD:
 FINISH: _____
 THICKNESS: _____
 TYPE: _____
 CHANNEL GUARDS SUPPLIED IN STANDARD .063" THICKNESS, TYPE 5005 H34 ALLOY WITH CLEAR ANODIZE.
 OPTIONAL .080" THICKNESS AND TYPE 5005 H34 ALLOY WITH MILL FINISH ARE ALSO AVAILABLE. PLEASE ADVISE IF AN OPTIONAL THICKNESS OR FINISH IS REQUIRED.
 OPTIONAL POWDER COAT FINISHES ARE AVAILABLE. PLEASE ADVISE OPTIONAL POWDER COAT FINISH IF REQUIRED.

UNITS REQ'D	UNIT HEIGHT	ANGLE	LEG LEN.	NOSE RAD.	WALL WIDTH


NOTES:

- CHANNEL GUARDS ARE SHIPPED WITH A PROTECTIVE STRIPPABLE COATING.
- CHANNEL GUARDS HAVE A STANDARD ANGLE OF 90°, LEG LENGTH OF 3 1/2" [89.0mm] AND A STANDARD NOSE RADIUS OF 3/16" [4.8mm], PLEASE ADVISE IF A DIFFERENT ANGLE, LEG LENGTH OR NOSE RADIUS IS DESIRED.
- CHANNEL GUARDS HAVE A MINIMUM LEG LENGTH OF 1" [25.4mm], A MINIMUM FINISHED WALL WIDTH OF 4-7/8" [123.8mm], AND MINIMUM NOSE RADIUS OF 3/16" [4.8mm]
- ANGLES ONLY AVAILABLE BETWEEN 45° - 178°.
- *CHANNEL GUARDS CAN BE USED AT FULL OR PARTIAL HEIGHTS. PLEASE ADVISE SPECIFIED UNIT HEIGHT OF CHANNEL GUARD.*



ASCO-8 SERIES CORNER GUARD WITH ADHESIVE

WALL CONDITION	SPECIFIED FASTENER	QUANTITY	CS PART NUMBER
STEEL STUD/GYPSUM WALL CONCRETE/CONC. BLOCK WOOD STUD/GYPSUM WALL	OA12 STRUCTURAL ADHESIVE (85 L/F COVERAGE PER TUBE)	28 FL. OZ	90M196001

 <p>Construction Specialties™ Hughesville, PA 800.233.8493 570.546.5941 Mississauga, ON 888.895.8955 905.274.3611 www.c-sgroup.com © Copyright 2017 Construction Specialties, Inc.</p>	PROJECT:	REVISION:
	JOB NO.:	F&F:
	CUSTOMER:	
	REP:	DATE:
	DRAWN BY:	SHEET NO: