

NO.	REVISION	DATE	BY
NO.	F&F RELEASE	DATE	BY

PART NUMBER:



Technical drawing of the extruded end trim assembly. The drawing shows a cross-section of the assembly with the following dimensions and components:

- PEDITRED LENGTH**: Indicated by a dimension line at the top.
- TRAFFIC DIRECTION**: Indicated by an arrow pointing left.
- 3/4" [19.1mm]**: Dimension for the top flange of the extruded end trim.
- 1 1/2" [38.2mm]**: Dimension for the spacing between the punched connectors.
- 11/16" [17.5mm]**: Dimension for the height of the aluminum rail.
- 3/16" MASONRY LAG FASTENER (90H066004)**: Indicated by a callout pointing to the fastener.
- 24" (609.6mm) O.C.**: Dimension for the spacing between the fasteners.
- ALUMINUM RAIL (16A077XXX)**: Indicated by a callout pointing to the rail.
- PUNCHED CONNECTOR TPE (16V055108)**: Indicated by a callout pointing to the connector.
- EXTRUDED END TRIM TPE (16V052108)**: Indicated by a callout pointing to the trim.

\*ADDITIONAL SPECIFICATIONS ARE CONTAINED IN THE LATEST C/S CATALOG OR AT C-SGROUP.COM AND ARE CONSIDERED PART OF THIS TRANSMITTAL.



6696 Route 405 Highway, Muncy PA 17756  
(800) 233-8493 • Fax (570) 546-4692 • [www.c-sgroup.com](http://www.c-sgroup.com)

PLEASE VERIFY ALL	QTY	MARK #	LOCATION	MODEL	DIM 'A' WIDTH	DIM 'B' LENGTH	FINISH	NOTES

PROJECT:		
LOCATION:		
CONTRACTOR:		
AGENT:		SHT:
DRG. BY:	DATE:	JOB NO.: