

## Door Frame Protection

Custom-formed door frame protectors feature durable Acrovyn® to protect interior door frames from constant wear and tear.

### Advantages

- Multiple models available for specific design and function needs, including shock absorption
- Reduces the need for constant repair and painting, which takes time and can be costly
- Extends the life cycle of the frame
- Available in all Acrovyn standard solid colors, woodgrains & brushed metal finishes to help coordinate with any interior design scheme

### Applications

- Interior openings that see constant wear & tear on door frames

### Building Segments

- Healthcare
- Senior Living
- Education
- Hospitality
- Retail
- Sports & Entertainment
- Aviation & Transportation



[View 3D Model →](#)



# Door Frame Protection

## Product Details

- Adhesive mount
- PVC-free Acrovyn
- A & B models thermoformed from .040" (1.02mm) thick Acrovyn in suede texture
- D model features .078" (1.98mm) thick Acrovyn cover with Acrovyn top & bottom end caps in shadowgrain texture. (Rear portion of D2 is suede texture). End caps available in solid colors only
- D model fits recessed frames having 2¼" (57.2mm) recess from face of door frame to door stop. Include continuous aluminum retainer
- 4' (1.2m) height standard; 32-114" (0.8-2.9m) heights available
- Self-adhesive tape model available
- Fire-rating heat stamp

## Warranty

- Acrovyn Doors Limited Lifetime Warranty

## Acrovyn Finish Options



See all finish options online at [c-sgroup.com](http://c-sgroup.com).

## Certifications / Testing

- Resistant to certain bacterial & fungal growth (per ASTM G 22-76 & G 21-96)
- Chemical resistant (per ASTM D543-06)
- Taber abrasion resistant (per ASTM D 4060-07) (suede & shadowgrain textures only)
- Fire test standards: UL-10C (Acrovyn models only)



See Door Frame Protectors →



## Model Details

| MODEL  | CROSS SECTION | DESCRIPTION   | MODEL  | CROSS SECTION | DESCRIPTION   |
|--------|---------------|---|--------|---------------|---|
| A1-DFP |               | Two-piece. 1⅜" (34.9mm) doors. Includes parts 1600 & 1500. Supplied to part dimensions.                                     | B2-DFP |               | One-piece. Flush frame to wall configurations. Supplied to field-verified dimensions only. Hospital stops available.  |
| A2-DFP |               | Two-piece. 1¾" (44.5mm) doors. Includes parts 1600 & 2000. Supplied to part dimensions.                                     | D1-DFP |               | One-piece. Heavy-duty, shock-absorbing protection for lead-in frame edges.  |
| B1-DFP |               | One-piece. Extended frame model with returns to wall. Supplied to field-verified dimensions only. Hospital stops available. | D2-DFP |               | One-piece. Heavy-duty, shock-absorbing protection for lead-in frame edges and extra rear protector. Part 1500: 1 ⅜" (34.9mm) doors. Part 2000: 1 ¾" (44.5mm) doors. |