

ASM-S & ASMC-S Series

Technical Data:

Aluminum


- Extrusion – CS uses multiple alloys & tempers which are established to be the most appropriate for the given use of individual parts. Will be one of the following: (6063-T5, T6, T52) (6061-T5, T6, T51) (6105-T5, T6) (6005-T5) (6005A-T5, T6), ASTM B221

Duroflex Gasket

- Single Durometer – 80 Shore A, ASTM D2000
- Color - Gray

Stainless Steel

- Type 304 ASTM A167, A240A, A240M



MODEL	JOINT WIDTH	MINIMUM OPENING	MAXIMUM OPENING	EXPOSED SURFACE	BLOCKOUT WIDTH	BLOCKOUT HEIGHT
ASM-100S/B	1.00" (25mm)	0.38" (10mm)	1.50" (38mm)	3.13" (80mm)	N/A	N/A
ASM-200S/B	2.00" (51mm)	0.38" (10mm)	3.00" (76mm)	4.63" (118mm)	N/A	N/A
ASM-300S/B	3.00" (76mm)	0.38" (10mm)	6.00" (152mm)	7.63" (194mm)	N/A	N/A
ASM-400S/B	4.00" (102mm)	0.38" (10mm)	6.00" (152mm)	7.63" (194mm)	N/A	N/A
ASMC-100S/B	1.00" (25mm)	0.50" (13mm)	1.50" (38mm)	1.88" (48mm)	N/A	N/A
ASMC-200S/B	2.00" (51mm)	0.50" (13mm)	3.00" (76mm)	3.38" (86mm)	N/A	N/A
ASMC-300S/B	3.00" (76mm)	0.50" (13mm)	6.00" (152mm)	6.38" (162mm)	N/A	N/A
ASMC-400S/B	4.00" (102mm)	0.50" (13mm)	6.00" (152mm)	6.38" (162mm)	N/A	N/A

