


STORM RESISTANT LOUVER MODEL RS-9615



PLAN VIEW (SEE SHEET 2 FOR VERTICAL SECTION)
NTS

SCREENS

- SCREEN NOT REQUIRED
- SCREEN REQUIRED
- INTERIOR MOUNTED
- EXTERIOR MOUNTED
- BIRDSCREEN: 1/2" MESH .063 DIA. ALUM. WIRE (MILL FINISH)
- INSECT SCREEN: 18x16 ALUM. MESH (MILL FINISH)

FINISHES

- STANDARD MILL
- FLUOROPOLYMER POWDER COAT (NOT AVAILABLE IN 600XL OR 700)
- KYNAR (500),(600XL)or(700)
- (1) OF CS STD. COLORS
- CUSTOM COLOR, CS REQUIRES A COLOR CHIP FOR MATCHING
- BRONZE ANODIC (DARK OR MED.)
- CLEAR ANODIZE
- OTHER _____

CS EXTRUDER ALUMINUM STORM RESISTANT LOUVER MODEL RS-9615. FRAMES AND BLADES TO BE FABRICATED FROM 6063-T6 ALLOY, WITH REINFORCING BOSSES. ALL FASTENERS TO BE STAINLESS STEEL.

UNSUPPORTED BLADE LENGTH= @ PSF.

MARK	QTY.	"A" DIM.	"B" DIM.	NUMBER OF MULLIONS	LOUVER LOCATION	REMARKS

Construction Specialties, Inc.
3 Werner Way
Lebanon, New Jersey 08833
800-233-8493

PROJECT:

CUSTOMER:

ARCH'T:

AGENT:


CKD.
BY:
DRAWN
BY:

DATE:

DWG.
NO:

SHEET 1 OF 2

STORM RESISTANT LOUVER MODEL RS-9615



VERTICAL SECTION (SEE SHEET 1 FOR PLAN SECTION)
(NTS)

MARK	QTY.	"A" DIM.	"B" DIM.	NUMBER OF MULLIONS	LOUVER LOCATION	REMARKS
						CKD. BY:
Construction Specialties, Inc. 3 Werner Way Lebanon, New Jersey 08833 800-233-8493				PROJECT:	DRAWN BY:	
				CUSTOMER:	DATE:	
				ARCH'T:	DWG. NO:	
				AGENT:	SHEET 2 OF 2	